

Mosaic Installation Guidelines

Please inspect product before installation. No claims will be accepted after installation.

Grout Selection: Non-sanded grout is recommended for any installation with a grout joint less than 1/8", wall installations, and products with glass or metal finishes. Sanded grout is recommended for most installations with a grout joint more than 1/8" and floor installations.

Grout Preparation & Application: Please consult grout preparation and application instructions provided by the grout manufacturer before using grout.

Grout Clean-up: With a dry lint-free cloth, remove excess grout from tile surface. Then with a clean sponge dampened with warm water, continue to clean the tile surface of grout. Once the tile surface appears clean, wipe down again with a fresh damp sponge to remove any grout film. After 15 minutes, buff the tile surface with a soft cloth.

Tile and Grout Sealing: Allow the installation to dry for 2 days. Inspect tile surface for remaining grout film and residue. A grout haze remover may be used for removing stubborn residue. Please consult grout haze remover instructions provided by the manufacturer before using grout haze remover. Test a precautionary section of the tile surface before using grout haze remover. Allow the clean tile surface to dry before applying grout sealant. Please consult grout sealant instructions provided by the manufacturer before using grout sealants.

Stainless Steel and Aluminum Mosaics: Use quartz-free, flexible, plasticized joint sealers for non-absorbent materials for jointing to avoid scratches on the surface. Cut the material with a wet cutting device at the rear in order to prevent uneven edges. Cut edges can be treated and smoothed using fine sand paper or a metal file.

NOTICE: The information provided above are suggested guidelines and do not imply warranty.

DISCLAIMER: We guarantee that all of our products are sold as advertised. Some porcelain products may be labeled with ceramic descriptions, as ceramic is a type of porcelain.

Mosaic Installation Guidelines

Please inspect product before installation. No claims will be accepted after installation.

Grout Selection: Non-sanded grout is recommended for any installation with a grout joint less than 1/8", wall installations, and products with glass or metal finishes. Sanded grout is recommended for most installations with a grout joint more than 1/8" and floor installations.

Grout Preparation & Application: Please consult grout preparation and application instructions provided by the grout manufacturer before using grout.

Grout Clean-up: With a dry lint-free cloth, remove excess grout from tile surface. Then with a clean sponge dampened with warm water, continue to clean the tile surface of grout. Once the tile surface appears clean, wipe down again with a fresh damp sponge to remove any grout film. After 15 minutes, buff the tile surface with a soft cloth.

Tile and Grout Sealing: Allow the installation to dry for 2 days. Inspect tile surface for remaining grout film and residue. A grout haze remover may be used for removing stubborn residue. Please consult grout haze remover instructions provided by the manufacturer before using grout haze remover. Test a precautionary section of the tile surface before using grout haze remover. Allow the clean tile surface to dry before applying grout sealant. Please consult grout sealant instructions provided by the manufacturer before using grout sealants.

Stainless Steel and Aluminum Mosaics: Use quartz-free, flexible, plasticized joint sealers for non-absorbent materials for jointing to avoid scratches on the surface. Cut the material with a wet cutting device at the rear in order to prevent uneven edges. Cut edges can be treated and smoothed using fine sand paper or a metal file.

NOTICE: The information provided above are suggested guidelines and do not imply warranty.

DISCLAIMER: We guarantee that all of our products are sold as advertised. Some porcelain products may be labeled with ceramic descriptions, as ceramic is a type of porcelain.